

i tape



INTERPACK
BRAND PACKAGING SYSTEMS



CE-12P

CASE ERECTOR WITH POWERED HOPPER

Interpack's CE Series Vertical Format Case Erectors are operator free, automatic machines that will form a knocked down uniform sized case, fold the bottom four flaps and apply pressure sensitive carton sealing tape to the bottom of RSC or HSC style cases. Every Interpack Case Sealer comes with an ET 2Plus tape head with adaptive technology to provide optimal tape application and wipe down to each of the 3 taped panels of the case.

These value priced machines offer significant productivity gains over manual case erecting as well as addressing the effects of strain related illness or repetitive motion issues.

These vertical format case erectors offer an expanded range of case sizes versus horizontal format erectors. Their compact footprints conserve floor space while improving productivity.




ET 2Plus tape head

MACHINE FEATURES & BENEFITS

- Processes up to 12 cases per minute
- Folds four bottom flaps pneumatically in the stationary position
- Rapid case size set up with no tools or change parts
- Standard casters, case on demand eye, low tape and no tape detection
- Analog counters simplify case size set up
- Powered hopper has 48" of capacity (approx. 135-150 RSC cases)
- Up to six vacuum cups positively withdraw the case from the hopper
- Powered hopper lift
- Visual and audible alarms for case erect failure
- Spring loaded side belt drive propels the case through case taping

Scan for more information on Interpack's CE Series, including CAD drawings, manuals and videos!



800-972-4675 | itape.com

ipg®
intertape
polymer
group®

PRODUCT ATTRIBUTES

| CHARACTERISTICS | CE-12P | CE-12P/3" |
|-----------------------------|-------------------------------------|-------------------------------------|
| Min Case (L x W x H) | 10" x 7" x 4" | 10" x 7" x 4" |
| Max Case (L x W x H) | 23" x 16" x 22" | 23" x 16" x 22" |
| Case Weight | N/A | N/A |
| Cases per Minute | 12 | 12 |
| Electric | 110v., 1ph., 60hz., 5A., (2 x ¼ HP) | 110v., 1ph., 60hz., 5A., (2 x ¼ HP) |
| Compressed Air Requirements | 10CFM @90PSI | 10CFM @90PSI |
| Tape Width | 36 - 48 mm (1.5" - 2") | 48 - 72 mm (2" - 3") |
| Conveyor Height | 25" | 25" |
| Machine Weight | 1,675 lbs | 1,675 lbs |
| Machine Dimensions | 86" x 96" x 62" | 86" x 96" x 62" |



1 Pneumatic arm squares cases before sealing



2 All 4 flaps folded pneumatically



3 Analog counters simplify changeover



4 48" powered hopper holds up to 150 cases



5 Powered hopper lift



6 Low tape/no tape motion sensors



7 Automatic and Manual mode operation with failure diagnostic LED readout

OPTIONS & ACCESSORIES

- 3-inch wide tape heads
- Tape head spare parts kit
- Factory installation
- ET Xtreme™ tape heads



Factory installation



Special electrics

DID YOU KNOW?

IPG® is the only North American manufacturer of all 3 types of pressure-sensitive adhesives. Combine Interpack™ machinery and IPG long roll pressure-sensitive tape for greater value. Contact your authorized IPG distributor for details.



Scan for more info or visit itape.com/machines

